

STANDARD & COMMERCIAL PIPE HANGERS

A 235 Standard Clevis Hanger

Material: Zinc Plated carbon steel. Also

available in Stainless Steel and Bare

Metal.

Application: Designed for suspending non -

insulated stationary pipe, allowing


for vertical adjustment.

Ordering: Specify pipe size and figure number.

Approvals : Complies with Manufacturers

Standardization Society SP - 69

Type 1









Listed and approved in 1" thru 8" only

A 235 STANDARD DUTY CLEVIS HANGER															
SIZE		"A"		"В"		"C"		D		Lower Material		Upper Material		Max	Вох
in	mm	in	mm	in	mm	in	mm	ın	mm	in	mm	in	mm	Rec Load	Qty
1/2	13	3/8	10	2-7/8	73	2-3/8	61	1/4	6	1/8x1	3x25	1/8x1	3x25	610	50
3/4	19	3/8	10	3-3/16	80	2-9/16	66	1/4	6	1/8x1	3x25	1/8x1	3x25	610	50
1	25	3/8	10	3-3/8	86	2-11/16	68	1/4	6	1/8x1	3x25	1/8x1	3x25	730	50
1-1/4	32	3/8	10	3-3/4	95	2-3/4	73	1/4	6	1/8x1	3x25	1/8x1	3x25	730	50
1-1/2	38	3/8	10	4-1/16	103	3-1/16	78	1/4	6	1/8x1	3x25	1/8x1	3x25	730	50
2	50	3/8	10	4-1/2	114	3-1/4	83	1/4	6	1/8×1	3x25	1/8x1	3x25	730	50
2-1/2	64	1/2	13	5-1/2	140	4-1/16	103	3/8	10	3/16x1-3/16	5x30	3/16x1-3/16	5x30	1,350	25
3	76	1/2	13	6-1/8	155	4-5/16	109	3/8	10	3/16x1-3/16	5x30	3/16x1-3/16	5x30	1,350	25
3-1/2	89	1/2	13	6-3/4	171	4-11/16	119	3/8	10	3/16x1-3/16	5x30	3/16x1-3/16	5x30	1,350	25
4	102	5/8	16	7-5/8	193	5-5/16	135	3/8	10	3/16x1-3/16	5x30	1/4x1-3/16	6x30	1,430	25
5	25	5/8	16	8-7/8	225	6-1/16	153	1/2	13	3/16x1-3/16	5x30	1/4x1-3/16	6x30	1,430	1
6	32	3/4	19	10	254	6-5/8	169	1/2	13	3/16x1-1/2	5x38	1/4x1-1/2	6x38	1,940	1
8	38	7/8	23	12-3/4	324	8-3/8	213	5/8	16	3/16x1-1/2	5x38	1/4x1-1/2	6x38	2,000	1
10	50	7/8	23	16-5/8	423	11-1/4	286	3/4	19	1/4x2	6x50	5/16x2	8x50	3,600	-1
12	64	7/8	23	18-5/8	475	12-5/16	313	3/4	19	1/4x2	6x50	5/16x2	8x50	3,800	1
14	76	1	25	20-5/16	516	13-5/16	338	7/8	22	1/4x2	6x50	1/2x2	12x50	4,200	1
16	89	1	25	22-1/16	560	14	355	1	25	1/4x2-1/2	6x63	1/2x2-1/2	12x63	4,600	_ 1
18	38	1	25	24-3/4	628	15-11/16	399	1-1/8	28	1/4x2-1/2	6x63	1/2x2-1/2	12x63	4,800	1
20	50	1-1/4	32	27-3/8	695	17-3/4	441	1-1/4	32	5/16x3	8x76	5/8x3	16x76	4,800	1
24	102	1-1/4	32	31-5/8	803	19-5/8	498	1-1/4	32	5/16x3	8x76	5/8x3	16x76	4,800	1



